

# ATTENUATORS 1 W

0-1 GHz

## DESCRIPTION

- This 1 W series include 3 dB, 10 dB, 20 dB and 30 dB attenuators.
- This series of attenuators have very low SWR and are especially suitable for use with:
  - Coaxial Transmission Lines
  - Power Monitors
  - Wattmeters.



PRO-ATT-...-1-1-BNC

## SPECIFICATIONS

ELECTRICAL	
MODEL	PRO-ATT-...-1-1-BNC
FREQ.RANGE	0 - 1 GHz
MAX. INPUT POWER	1W
ATTENUATION	3, 10, 20 or 30 dB Other attenuation values on request
VAR. on ATTENUATION	± 0.5 dB
IMPEDANCE	Nom. 50 Ω
SWR	≤ 1.25
MECHANICAL	
TEMP. RANGE	-30°C → +60°C
CONNECTORS	BNC-female - BNC-female
DIMENSIONS	∅19.5 x 66 mm
WEIGHT	Approx. 30 g

## ORDERING DESIGNATION

MODEL	PRODUCT NO.	ATTENUATION VERSION
PRO-ATT-3-1-1-BNC	200 000 998	3 dB
PRO-ATT-10-1-1-BNC	200 001 036	10 dB
PRO-ATT-20-1-1-BNC	200 001 028	20 dB
PRO-ATT-30-1-1-BNC	200 001 037	30 dB



PROCOM A/S reserve the right to amend specifications without prior notice.

19/07/2010