

GA 70/...-IC-F61

Rubber Antenna for ICOM Portable Equipment
in the 70 cm Band



TETRA

DESCRIPTION:

- ★ Sturdy, conical, flexible rubber antenna.
- ★ Full-size $1/4 \lambda$ whip.
- ★ Highest quality materials – designed for “wear and tear”.
- ★ Delivered factory tuned and tested to ensure minimum SWR.
- ★ Especially designed for ICOM IC-F61 (450 MHz band).

ORDERING DESIGNATIONS:

FREQUENCY	380–430 MHz	400–450 MHz	420–470 MHz
TYPE NO.	GA 70/s-IC-F61	GA 70/l-IC-F61	GA 70/h-IC-F61

SPECIFICATIONS:

ELECTRICAL	
MODEL	GA 70/...-IC-F61
ANTENNA TYPE	$1/4 \lambda$ antenna for portable equipment
FREQUENCY	70 cm band covered by three models
IMPEDANCE	Nom. 50 Ω
POLARISATION	Vertical
GAIN	0 dB (equal to a $1/4 \lambda$ portable antenna)
BANDWIDTH	≥ 60 MHz @ SWR ≤ 2.5
SWR	≤ 2 when mounted directly on portable equipment
MAX. POWER	100 watt
MECHANICAL	
MATERIALS	Steelwire moulded in thermoplastic rubber Environment-proof plastics Black-chromed brass
COLOUR	Black
TOTAL HEIGHT	Approx. 140 mm (dep. on type)
WEIGHT	Approx. 30 g
CONNECTOR	SMA (male) special for IC-F61

