







PRODUCT		ORDER No.
	<p>PROCOM 24 GHz Parabolic Antenna 36 dBd, Dia. = 48 cm, F/D = 0.4. Completely assembled parabolic dish antenna, white coated, with band designation, waveguide, flange and feed horn. SWR at f_0: < 1.25. Opening angle: 2.5°.</p>	<p>PRO-24-001</p>

PRODUCT		ORDER No.
	<p>PROCOM 24 GHz Parabolic Dish Dia. = 48 cm, F/D = 0.4. White coated but without text and without central hole for waveguide feedthrough.</p>	<p>PRO-24-002</p>

PRODUCT		ORDER No.
	<p>PROCOM 24 GHz Waveguide Section, WR 42, made of brass. L = 240 mm (length suiting parabolic dish antenna). Frequency range: 18 - 26.5 GHz</p>	<p>PRO-24-004</p>

PRODUCT		ORDER No.
	<p>PROCOM 24 GHz Flange for WR 42, made of brass.</p>	<p>PRO-24-006</p>

PRODUCT		ORDER No.
	<p>PROCOM 24 GHz Quick-Coupling Flange, made of brass. For fast fitting of dish to transverter (with 4 longnuts).</p>	<p>PRO-24-007</p>

PRODUCT		ORDER No.
	<p>PROCOM 24 GHz Coaxial/Waveguide Transition (SMA-female connector). Made of gilt brass. SWR at f_0: < 1.3.</p>	<p>PRO-24-008</p>